
506X Variants

IMPACT 5000 Series

IMPACT SDW 5066 is a double-sided wireless DECT headset for modern office professionals, providing next generation communication quality, future-proof device flexibility, all-day wearing comfort and advanced security to modern work environments.













sound

Super wideband audio and

noise-cancelling system for

clear speech in noisy offices

unique two microphone

Key Features

Get all-day wearing comfort

With soft leatherette ear pad and a choice of wearing styles for consistent comfort and wellbeing to increase efficiency

Empower your people with total flexibility

One flexible headset that pairs easily to all devices with extensive wireless range up to 180 m/590 ft



Ensure enhanced security for all your calls


With Protected Pairing, 128-bit authentication, DECT Security certification and EPOS Manager

See more at eposaudio.com/IMPACT-5000


What's in the Box




How to Use the **IMPACT 5000**



Accept/end a call





Additional benefits & features



Discover exceptional speech intelligibility

With two-microphone noise-cancelling system and own-voice detection technology



Ensure clear calls with certified solutions

Optimized for UC



Benefit from triple-connectivity

Manage all calls from one headset via PC/softphone, desk and mobile phone



Set up and manage your system with ease

Using EPOS Manager for easy control of the DECT system



Talk for longer

Extended talk time of up to 14 hours narrowband



Manage calls seamlessly

With smart headset and base station controls and easy conferencing option



Stay mobile around the office

With fast charging – 50% battery charges in just 30 minutes



Protect your hearing

From acoustic shock with EPOS ActiveGard® technology



Enjoy high-quality music and multimedia

With stereo sound that takes DECT headsets to the next level

Product data

1/3

General			
Wearing style	Double-sided headset		
Headset weight	136 g / 4.80 oz		
Warranty	2 years		
DECT	1.880 to 1.900 MHz (EU, UK, AUS) 1.920 to 1.930 MHz (US)		
Audio			
Speaker frequency response	150 Hz - 11.5 kHz (Super wideband) 150 Hz - 7,5 kHz (Standard wideband and High density wideband) 150 Hz - 3.5 kHz (Narrowband) 20 Hz - 20 kHz (Fullband - music mode)		
Microphone type	Digital MEMs microphones - two microphone noise-cancelling system for exceptional speech clarity		
Microphone frequency response	100 Hz - 11.0 kHz (Super wideband) 100 Hz - 7.5 kHz (Wideband) 150 Hz - 3.5 kHz (Narrowband)		
Noise cancellation	Two microphone noise-cancelling system		
Technical			
Charging time	O - 50 %: 30 minutes / 0 - 100 %: 1 hour and 30 min		
Standby time	Up to 44 hours		
Talk time	Up to 14 hours (Narrowband) Up to 12 hours (Density optimized wideband) Up to 11,5 hours (Wideband) Up to 9 hours (Super wideband)		
Range	Line of sight: 180 m / 590 ft		

Typical office building: 55 m / 180 ft

Product data

2/3

Product variants	What's in the box		
SDW 5066/5065	Base station SDW 5 BS, headset, BTD 800 USB dongle (Included in SDW 5066), USB cable, power supply, audio phone cable, quick guides (headset and base station), safety guide, compliance sheet		
SDW 5063	Base station SDW 3 BS, headset, BTD 800 USB dongle, USB cable, power supply, audio phone cable, printed quick guides (headset and base station), safety guide, compliance sheet		
Software			
EPOS devices can be managed with following Software solutions:			
EPOS Connect	Conduct firmware updates and configure headsets for personal audio preferences. EPOS Connect works for Windows, Mac® and VDI/Thin client environments: eposaudio.com/software-epos-connect		
EPOS Manager	Manage, update and configure EPOS audio devices from any location - For both cloud and on-premises solutions: eposaudio.com/software-epos-manager		

Product data

3/3

Product	Connects to	Certifications	EAN code	UPC code
SDW 5066 - EU/UK/AUS Art. no. 1001026	Desk phone, PC/Softphone, mobile devices	Optimized for UC and certified for Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 OO828 6	8 40064 40828 8
SDW 5066 - US Art. no. 1000629	Desk phone, PC/softphone, mobile devices	Optimized for UC and certified for Google Meet, Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 00430 1	8 40064 40430 3
SDW 5065 - EU/UK/AUS Art. no. 1001023	Desk phone, PC/softphone	Optimized for UC and certified for Google Meet, Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 00825 5	8 40064 40825 7
SDW 5065 - US Art. no. 1000605	Desk phone, PC/softphone	Optimized for UC and certified for Google Meet, Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 00406 6	8 40064 40406 8
SDW 5063 - EU/UK/AUS Art. no. 1001017	PC/softphone	Optimized for UC and certified for Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 00819 4	8 40064 40819 6
SDW 5063 - US Art. no. 1000593	PC/softphone	Optimized for UC and certified for Webex, Avaya, Alcatel-Lucent Enterprise, Enreach	57 14708 00394 6	8 40064 40394 8

Spare parts

1/1

Product	Art. no.	Description	EAN code	UPC code
SDW D1 Accessory Pack	1000982	Carry pouch and USB-A charging cable for IMPACT 5000 headsets	57 14708 00784 5	8 40064 40784 7
SDW D1 USB	1000299	USB DECT dongle	57 14708 00100 3	8 40064 40100 5
SDW D1 USB - US	1000978	USB DECT dongle	57 14708 00780 7	8 40064 40780 9
SDW 60 HS	1000663	Double-sided headset for SDW 5066, SDW 5065 and SDW 5063	57 14708 00434 9	8 40064 40434 1
SDW 5 BS - EU/UK/AUS	1001027	Base station for SDW 5066 and SDW 5065 (without BTD 800 dongle)	57 14708 00829 3	8 40064 40829 5
SDW 5 BS - US	1000681	Base station for SDW 5066 and SDW 5065 (without BTD 800 dongle)	57 14708 00482 0	8 40064 40482 2
SDW 3 BS - EU/UK/AUS	1001028	Base station for SDW 5063 (without BTD 800 dongle)	57 14708 00830 9	8 40064 40830 1
SDW 3 BS - US	1000685	Base station for SDW 5063 (without BTD 800 dongle)	57 14708 00486 8	8 40064 40486 0
-		 -	_	

Appendix

1/1

Additional product data

Weight	136 g / 4.80 oz	
Ear pad size	ø 54,5 mm / 2.15 in	
Personalization	Yes with nameplate on headset	
Speaker type	High-quality Neodymium Magnet Speaker for outstanding audio quality	
GAP compatible	Yes (Headset)	
BTD 800 USB dongle	For more information please see eposaudio.com/btd-800-usb (Included in SDW 5066)	
USB-A port	Supports call handling with EPOS devices and smartphone charging	
Temperature range	Operational: +5 °C to + 45 °C / +41 °F to +113 °F Storage: -20 °C to + 70 °C / -4 °F to +158 °F	
Battery (lithium polymer)	Exchangeable by service	
Listen time (music mode)	Up to 9 hours (Fullband)	
Auto sleep mode when out of range	Yes, after 12 hours	
EPOS ActiveGard® technology	Protect users against acoustic injury caused by sudden sound burst on the line	
EU*/AUS Limiter depending on regional variant	Activation by dip switch, EPOS Connect and EPOS Manager software	
Pairing intrusion protection	Protected pairing	
Certification	DECT Security certified	
EPOS Connect	Remote call control, firmware updates and settings: eposaudio.com/software-epos-connect	
PC Software	For other relevant PC software, please check: eposaudio.com/software	
EPOS Manager	Manage, update and configure your EPOS audio devices from one location: eposaudio.com/software-epos-manager	

^{*} Noise At Work: The EU's "Noise At Work Directive" (2003/10/EC) sets limits for two types of noise in the workplace: Acoustic burst and Sustained Noise.